


General Description

These N-Channel enhancement mode power field effect transistors are using trench DMOS technology. This advanced technology has been especially tailored to minimize on-state resistance, provide superior switching performance, and withstand high energy pulse in the avalanche and commutation mode. These devices are well suited for high efficiency fast switching applications.

SOT723 Pin Configuration



BVDSS	RDSON	ID
20V	300mΩ	800mA

Features

- 20V,800mA, $R_{DS(ON)} = 300m\Omega @ V_{GS} = 4.5V$
- Improved dv/dt capability
- Fast switching
- Green Device Available
- Suit for 1.5V Gate Drive Applications

Applications

- Notebook
- Load Switch
- Battery Protection
- Hand-held Instruments

Absolute Maximum Ratings $T_c=25^\circ C$ unless otherwise noted

Symbol	Parameter	Rating	Units
V_{DS}	Drain-Source Voltage	20	V
V_{GS}	Gate-Source Voltage	± 8	V
I_D	Drain Current – Continuous ($T_A=25^\circ C$)	800	mA
	Drain Current – Continuous ($T_A=70^\circ C$)	640	mA
I_{DM}	Drain Current – Pulsed ¹	3.2	A
P_D	Power Dissipation ($T_A=25^\circ C$)	450	mW
	Power Dissipation – Derate above $25^\circ C$	3.6	mW/ $^\circ C$
T_{STG}	Storage Temperature Range	-55 to 150	$^\circ C$
T_J	Operating Junction Temperature Range	-55 to 150	$^\circ C$

Thermal Characteristics

Symbol	Parameter	Typ.	Max.	Unit
$R_{\theta JA}$	Thermal Resistance Junction to ambient	---	280	$^\circ C/W$

Electrical Characteristics (T_J=25 °C, unless otherwise noted)
Off Characteristics

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V , I _D =250uA	20	---	---	V
ΔBV _{DSS} /ΔT _J	BV _{DSS} Temperature Coefficient	Reference to 25°C , I _D =1mA	---	-0.01	---	V/°C
I _{DSS}	Drain-Source Leakage Current	V _{DS} =20V , V _{GS} =0V , T _J =25°C	---	---	1	uA
		V _{DS} =16V , V _{GS} =0V , T _J =125°C	---	---	10	uA
I _{GSS}	Gate-Source Leakage Current	V _{GS} =±8V , V _{DS} =0V	---	---	±10	uA

On Characteristics

R _{DS(ON)}	Static Drain-Source On-Resistance	V _{GS} =4.5V , I _D =0.5A	---	200	300	mΩ
		V _{GS} =2.5V , I _D =0.4A	---	300	450	
		V _{GS} =1.8V , I _D =0.2A	---	500	700	
		V _{GS} =1.5V , I _D =0.1A	---	800	1200	
V _{GS(th)}	Gate Threshold Voltage	V _{GS} =V _{DS} , I _D =250uA	0.3	0.5	0.85	V
ΔV _{GS(th)}	V _{GS(th)} Temperature Coefficient		---	3	---	mV/°C

Dynamic and switching Characteristics

Q _g	Total Gate Charge ^{2, 3}	V _{DS} =10V , V _{GS} =4.5V , I _D =0.5A	---	1	2	nC
Q _{gs}	Gate-Source Charge ^{2, 3}		---	0.26	0.5	
Q _{gd}	Gate-Drain Charge ^{2, 3}		---	0.2	0.4	
T _{d(on)}	Turn-On Delay Time ^{2, 3}	V _{DD} =10V , V _{GS} =4.5V , R _G =10Ω I _D =0.5A	---	5	10	ns
T _r	Rise Time ^{2, 3}		---	3.5	7	
T _{d(off)}	Turn-Off Delay Time ^{2, 3}		---	14	28	
T _f	Fall Time ^{2, 3}		---	6	12	
C _{iss}	Input Capacitance	V _{DS} =10V , V _{GS} =0V , F=1MHz	---	38.2	75	pF
C _{oss}	Output Capacitance		---	14.4	28	
C _{rss}	Reverse Transfer Capacitance		---	6	12	

Drain-Source Diode Characteristics and Maximum Ratings

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
I _S	Continuous Source Current	V _G =V _D =0V , Force Current	---	---	0.8	A
I _{SM}	Pulsed Source Current		---	---	1.6	A
V _{SD}	Diode Forward Voltage	V _{GS} =0V , I _S =0.2A , T _J =25°C	---	---	1	V

Note :

1. Repetitive Rating : Pulsed width limited by maximum junction temperature.
2. The data tested by pulsed , pulse width ≤ 300us , duty cycle ≤ 2%.
3. Essentially independent of operating temperature.




Fig.1 Continuous Drain Current vs. T_c




Fig.2 Normalized $R_{DS(on)}$ vs. T_j




Fig.3 Normalized V_{th} vs. T_j




Fig.4 Gate Charge Waveform




Fig.5 Normalized Transient Response




Fig.6 Maximum Safe Operation Area




Fig.7 Switching Time Waveform





Fig.8 Gate Charge Waveform

SOT723 PACKAGE INFORMATION



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	MAX	MIN	MAX	MIN
A	0.4 BSC		0.016 BSC	
A1	0.8 BSC		0.031 BSC	
B	1.250	1.150	0.049	0.045
C	0.850	0.750	0.033	0.030
D	1.250	1.150	0.049	0.045
E	0.390	0.370	0.015	0.015
F	0.050	0.000	0.002	0.000
G	0.270	0.220	0.011	0.009
G1	0.250	0.170	0.010	0.007
H	0.150	0.080	0.006	0.003
I	13°	9°	13°	9°
L	0.250	0.150	0.010	0.006
J	11°	7°	11°	7°